

Lightning

micro-USB

Type-C

Charge & Sync any device, mobile or tablet !

- Sleek and stylish design: metal shell and flat TPE soft-touch cable
- Straight connectors, perfect for easy plug in
- Properly carries a 2.4 Amp charge (Lightning & micro-USB) and 3A (Type-C), enough to recharge a tablet, including an iPad Air
- Full line-up available to match your favorite companion:
 - USB-A to Lightning (Apple MFi certified)
 - USB-A to micro-USB connector
 - USB-A to Type-C 2.0
 - USB Type-C to Type-C 2.0
 - USB-A to Type-C 3.1 Gen2 (Fast Charge)
- 120cm/4" length ideal for work, home or auto charging

Tip: designed to be tangle-free, Emtec flat cables will spare you some troubles!



USB-A to Lightning

USB-A to microUSB

USB-A to Type C

Type-C to Type C

T700A



T700B



T700TC / T700TCU3*



T700C2



* USB 3.1 Gen2

- Stylish, elegant and sleek packaging design
- Premium quality packaging printed on smooth surface paper to add the perfect finishing touch to the product
- Pictograms clearly presenting the main product features and benefits
- Simple and efficient color code: Red for Lightning connector, blue for micro-USB connector and green for Type-C connectors

Technical specifications

Connector	USB-A to Lightning (Apple-certified) / micro-USB / or Type-C
Compatibility	Lightning version for any compatible Apple product using Lightning port Micro-USB version for any compatible device using micro-USB port Type-C version for any compatible device using Type-C port
Length	120 cm / 4" 100 cm / 3" for T700TCU3

Logistics

Référence produit	Description	EAN Unité	EAN 5 pces carton	EAN 40 pces carton
ECCHAT700AP	Emtec Cable USB-A to Lightning	3 126 170 158 413	3 126 170 158 420	3 126 170 158 437
ECCHAT700MB	Emtec Cable USB-A to micro-USB	3 126 170 158 383	3 126 170 158 390	3 126 170 158 406
ECCHAT700TC	Emtec Cable USB-A to Type-C 2.0	3 126 170 158 147	3 126 170 158 154	3 126 170 158 161
ECCHAT700TC2	Emtec Cable Type-C to Type-C 2.0	3 126 170 159 496	3 126 170 159 502	3 126 170 159 519
ECCHAT700TCU3	Emtec Cable USB-A to Type-C 3.1gen2	3 126 170 167 675	3 126 170 167 682	3 126 170 167 699